



40 Huntingwood Drive Huntingwood NSW 2148

Phone: (02) 8825 1999 Website: www.aeroflowperformance.com

AEROFLOW PERFORMANCE RADIATOR OVERFLOW TANK

WARNING!

THIS PRODUCT REQUIRES DETAILED KNOWLEDGE OF AUTOMOTIVE SYSTEMS. WE RECOMMEND THAT THIS INSTALLATION BE CARRIED OUT BY A QUALIFIED AUTOMOTIVE TECHNICIAN.

INTRODUCTION

Congratulations on your purchase of Aeroflow Performance fabricated alloy universal radiator overflow tank. Aeroflow Performance products cannot and will not be responsible for any damage, or other conditions resulting from misapplication of the parts described herein. However, it is our intention to provide the best possible products for our customer, products that perform properly and satisfy your expectations. Should you have any questions? Please call technical support at +61 2 8825 1900 and have the product part number on hand when calling.

This radiator overflow tank comes with our Billet 2" cap attached and can hold 800mL of fluid. The dimensions of this product are: Diameter 90mm (3-1/2") x Height 190mm (7-1/2").

This tank features two female -4AN O-ring fitting welded into bottom of tank. This tank also comes with two -4AN O-ring to 3/8 (9.52mm) barb fittings pre-installed. When installing radiator overflow tank ensure it is correctly mounted and secured to vehicle using appropriate methods. Make sure both mounting holes (M8x1.25mm) are used to secure the tank. Mounting bracket holes are centre to centre 80mm.

To plumb up this tank one fitting on tank should go to the radiator neck spout. The other barb will be attached to long tube that is mounted inside the overflow tank. This is an extra barb that is designed if the tank gets too full it needs to empty so pressure is not built up inside. Ensure to plumb this barb away from moving components or extreme heat sources to avoid any damages or accidents.



For more information or technical enquires

Contact: Aeroflow Performance on

Phone: (02) 8825 1979 Website: www.aeroflowperformance.com